

LAYBACK KERB



UPRIGHT KERB

KERB AND GUTTER WITH
KERB ADAPTOR

NOTES

1. PROPRIETRY KERB ADAPTOR TO SUIT K & G PROFILE INSTALLED IN ACCORDANCE WITH MANUFACTURERS REQUIREMENTS AND SHALL BE IN GALVANISED STEEL ONLY.
2. PIPE ACROSS FOOTPATH TO BE LAID WITH THE MAXIMUM AVAILABLE COVER, AND WITH A MINIMUM GRADE OF 1 IN 100.
3. REFER PROJECT DRAWINGS/SPECIFICATIONS FOR OPTION TO BE ADOPTED.
4. AT NEW DEVELOPMENTS SEAL INLET TO ADAPTOR.
5. ALL DIMENSIONS IN MILLIMETRES.
6. KERB ADAPTOR TO BE PROVIDED ON DOWNHILL SIDE OF EACH LOT

NOT TO SCALE

A	ORIGINAL ISSUE		3/10/06
REVISIONS		APP'D	DATE

STANDARD DRAWINGS

NORTHERN RIVERS LOCAL GOVERNMENT

KERB AND GUTTER
DRAINAGE CONNECTIONS

ROAD/STREET STANDARD DRAWING

R-08

A