



LEGEND

- SIGN POST IS TO BE LOCATED 250MM BEHIND NOMINAL KERB LINE.
- SIGN POST IS TO BE LOCATED 2000MM MIN. -4000MM MAX. FROM EDGE OF SEAL, OR AS DIRECTED BY THE SUPERINTENDENT.

SIGN STANDARD

A۷

 CL

 CT

CR

DR **ESP**

LN

PDE

PLRD

ST

TCE

BVD CIR

- 1. ROAD NAMES TO BE BLACK LETTERING (100mm) ON WHITE REFLECTIVE BACKGROUND - CLASS 1.
- 2. STREET NOS, ROAD NOS, OR 'NO THRU ROAD' TO BE BLACK LETTERING (25mm) ON WHITE REFLECTIVE BACKGROUND - CLASS 1.
- 3. ROAD NAMES TO BE MAX 13 LETTERS, WITH NO ABREVIATION OF MAIN NAMES

SIGN LOCATIONS

- 1. STREET NAMES MUST BE APPROVED BY COUNCIL.
- 2. SIGNS TO BE POSITIONED ON THE SIDE OF STREET AS DETAILED ABOVE.
- 3. CONCRETE N20 IN ACCORDANCE WITH AS 1379 AND AS 3600.
- 4. BARS φ10, GRADE 250 TO AS 1302.
- 5. ALL DIMENSIONS IN MILLIMETRES.

NOT TO SCALE

				Γ
				L
				1
		2		
Α	ORIGINAL ISSUE	JOH .	3/10/06	
	REVISIONS	APP'D	DATE	

DIA

300

PROPRIETARY DRIVE-IN METAL BASES MAY BE USED INSTEAD OF CONCRETE WHERE APPROVED BY COUNCIL.

NOTE

STANDARD DRAWINGS

NORTHERN RIVERS LOCAL GOVERNMENT

STREET NAME SIGN

ROAD/STREET STANDARD DRAWING